

Snap-In Patch Panels

Patch Panel 24 Snap-In Sliding White

Contact

LAN Systems (Nexans Cabling Solutions)
Phone: +44 (0)1256 486640
ncs.uk@nexans.com

Nexans ref.: [N521.663](#)

- Sliding mechanism
- Compatible with all Snap-In connectors
- 24 Snap-In ports with shutters
- Clip-on mechanism
- Exclusive Auto-Connect Earthing system
- Universal design supporting Unscreened and Screened connectors
- New Fully Painted Design

DESCRIPTION

Nexans Snap-In range of patch panels are designed to accommodate any of the Snap-In connectors in the LANmark product family (LANmark-7A, LANmark-7, LANmark-6A, LANmark-6, and LANmark-5).

The Snap-In panels feature an exclusive Clip-On system to secure the connector in the panel and to provide a simple means of earthing shielded connectors to facilitate installation. Connection of the panel to earth is achieved with a unique Auto-Connect feature removing the need for individual bonding conductors.

The panels also have a series of complementary cable management products such as blank panels and patch cord guides.

The sliding patch panels are designed for standard 19" enclosures, are 1U high, and support the following common features:

- 24 Ports with shutters
- Designed for Screened and Unscreened Snap-In connectors
- Compatible with all performance categories of connector
- Clip-On mechanism for simple earthing
- Exclusive rear cable management facilities
- Robust construction



LANmark

STANDARDS

International
Manufacturer specification

Snap-In Patch Panels

Patch Panel 24 Snap-In Sliding White

Contact

LAN Systems (Nexans Cabling Solutions)

Phone: +44 (0)1256 486640

ncs.uk@nexans.com

CHARACTERISTICS

Construction characteristics

Colour White

Material Steel

Dimensional characteristics

Heightunit 1 U

Depth 180 mm

Width 19 in

Usage characteristics

Field of application Fixed installations

Resistance to vibrations High

Mechanical Resistance Good mechanical resistance

Number of ports 24

Packaging Box